

GLISTEN

1. Product and Company Identification

Product Code: 4532
Product Name: GLISTEN
Revision: 06/24/2021
Supersedes Revision: 05/15/2017

Manufacturer Information: PDQ Manufacturing, Inc.
 201 Victory Circle
 Ellijay, GA 30540
Phone Number: (706)636-1848
Web site address: www.pdqonline.com

Emergency Contact: Chemtrec (800)424-9300 / 24 Hr.
 Leak, Spill, Exposure, Fire, Accident

Supplier Name and Address: **Phone Number:**

2. Hazards Identification

Skin Corrosion/Irritation, Category 1A
Serious Eye Damage/Eye Irritation, Category 2
Specific Target Organ Toxicity (single exposure), Category 3



GHS Signal Word: **Danger**

GHS Hazard Phrases: H314 - Causes severe skin burns and eye damage.
 H319 - Causes serious eye irritation.
 H335 - May cause respiratory irritation.

GHS Precautionary Phrases: P261 - Avoid breathing mist/vapors/spray.
 P264 - Wash hands thoroughly after handling.
 P271 - Use only outdoors or in a well-ventilated area.
 P280 - Wear protective gloves, protective clothing and eye protection.

GHS Response Phrases: P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P303+361+353 - IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison control center or physician for treatment advice. Have product container or label with you when calling poison control center or physician.
 P310 - Immediately call a POISON CENTER or doctor/physician.
 P321 - Specific treatment see section 4 on this SDS.
 P337+313 - If eye irritation persists, get medical advice/attention.
 P363 - Wash contaminated clothing before reuse.

GHS Storage and Disposal Phrases: P405 - Store locked up.
 P501 - Dispose of contents/container in accordance with all local, regional, national and international regulations.

SAFETY DATA SHEET**GLISTEN**

Potential Health Effects (Acute and Chronic):	Prolonged or repeated skin contact may cause dermatitis.
Inhalation:	Causes chemical burns to the respiratory tract. May be harmful if inhaled.
Skin Contact:	Causes skin burns. May cause deep, penetrating ulcers of the skin. May cause skin rash (in milder cases), and cold and clammy skin with cyanosis or pale color. Causes skin irritation.
Eye Contact:	Causes eye burns. May cause chemical conjunctivitis and corneal damage. Causes eye irritation.
Ingestion:	May cause severe and permanent damage to the digestive tract. Causes gastrointestinal tract burns. Causes severe pain, nausea, vomiting, diarrhea, and shock. May cause corrosion and permanent tissue destruction of the esophagus and digestive tract.

3. Composition/Information on Ingredients

CAS #	Hazardous Components (Chemical Name)	Concentration
1310-73-2	Sodium hydroxide {Caustic soda; Lye solution}	40.0 -55.0 %

4. First Aid Measures**Emergency and First Aid Procedures:**

In Case of Inhalation:	If breathing is difficult, give oxygen. Get medical aid. Remove from exposure and move to fresh air immediately.
In Case of Skin Contact:	Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Get medical aid.
In Case of Eye Contact:	Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.
In Case of Ingestion:	If victim is fully conscious, give a cupful of water. Never give anything by mouth to an unconscious person. Get medical aid.

5. Fire Fighting Measures**Flash Pt:**

Explosive Limits: LEL: UEL:

Autoignition Pt:

Suitable Extinguishing Media: Substance is noncombustible; use agent most appropriate to extinguish surrounding fire. Use water spray, dry chemical, carbon dioxide, or appropriate foam.

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Material will not burn. Use water spray to keep fire-exposed containers cool. Contact with metals may evolve flammable hydrogen gas. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

Flammable Properties and Hazards:

GLISTEN

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled:	Use proper personal protective equipment as indicated in Section 8. Spills/Leaks: Vacuum or sweep up material and place into a suitable disposal container. Avoid runoff into storm sewers and ditches which lead to waterways. Clean up spills immediately, observing precautions in the Protective Equipment section. Provide ventilation. Do not let this chemical enter the environment.
-------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

7. Handling and Storage

Precautions To Be Taken in Handling:	Wash thoroughly after handling. Keep container tightly closed. Avoid ingestion and inhalation. Discard contaminated shoes. Avoid contact with eyes, skin, and clothing.
Precautions To Be Taken in Storing:	Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from metals. Keep away from acids.

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
1310-73-2	Sodium hydroxide {Caustic soda; Lye solution}	PEL: 2 mg/m3	CEIL: 2 mg/m3	
Respiratory Equipment (Specify Type):	Respirator protection is not normally required.			
Eye Protection:	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.			
Protective Gloves:	Wear appropriate protective gloves to prevent skin exposure.			
Other Protective Clothing:	Wear appropriate protective clothing to prevent skin exposure.			
Engineering Controls (Ventilation etc.):	There are no special ventilation requirements. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.			

9. Physical and Chemical Properties

Physical States:	[] Gas [] Liquid [X] Solid		
Appearance and Odor:	.White solid block mild odor.		
Melting Point:	~ 150.00 F		
Boiling Point:			
Autoignition Pt:			
Flash Pt:			
Explosive Limits:	LEL:		UEL:
Specific Gravity (Water = 1):	> 1.0		
Vapor Pressure (vs. Air or mm Hg):			
Vapor Density (vs. Air = 1):			
Evaporation Rate:			
Solubility in Water:	Complete		
pH:	> 12		
Percent Volatile:			

SAFETY DATA SHEET

GLISTEN

10. Stability and Reactivity

Stability: Unstable [] Stable [X]

Conditions To Avoid - Instability: Avoid contact with acids, reducing agents, oxidizers, nitrogen oxides, amines, ammonia or other nitrogen containing compounds. contact with water. Incompatible materials.

Incompatibility - Materials To Avoid: Acids, Aluminum, Zinc.

Hazardous Decomposition or Byproducts: Toxic fumes of sodium oxide, Carbon monoxide, oxides of phosphorus, Carbon dioxide.

Possibility of Hazardous Reactions: Will occur [] Will not occur [X]

Conditions To Avoid - Hazardous Reactions:

11. Toxicological Information

Toxicological Information:

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
1310-73-2	Sodium hydroxide {Caustic soda; Lye solution}	n.a.	n.a.	n.a.	n.a.

12. Ecological Information

13. Disposal Considerations

Waste Disposal Method: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

RCRA P-Series: None listed.
RCRA U-Series: None listed.

14. Transport Information

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Corrosive solid, basic, inorganic, n.o.s. (Sodium hydroxide)

DOT Hazard Class: 8 CORROSIVE

UN/NA Number: UN3262 **Packing Group:** II



15. Regulatory Information

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
1310-73-2	Sodium hydroxide {Caustic soda; Lye solution}	No	Yes NA	No

Other US EPA or State Lists

1310-73-2 Sodium hydroxide {Caustic soda; Lye solution} CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No

GLISTEN

16. Other Information

Revision Date: 06/24/2021
Preparer Name: Regulatory Affairs

Hazard Rating System:

HEALTH	2
FLAMMABILITY	0
REACTIVITY	2
PPE	C

HMIS:

**Additional Information About
This Product:**

**Company Policy or
Disclaimer:**

The information contained in this Safety Data Sheet is provided pursuant to current OSHA regulations to convey information concerning the hazardous nature of the named product. The information supplied was compiled from the most reliable sources available at the time of preparation and in light of the most reasonable foreseeable exposure situations expected from the intended use of this product. The material(s) may present greater or lesser hazard exposure under other circumstances that are beyond the control of the manufacturer. Therefore it is imperative that all directions and warnings on the product label be read and closely followed.